Lecture 14: 10 March, 2022

Madhavan Mukund

https://www.cmi.ac.in/~madhavan

Data Mining and Machine Learning January–May 2022


Unsupervised learning


- Supervised learning requires labelled data
- Vast majority of data is unlabelled
- What insights can you get into unlabelled data?

"If intelligence was a cake, unsupervised learning would be the cake, supervised learning would be the icing on the cake "

> - Yann LeCun ACM Turing Award 2018







Applications

- Customer segmentation
 - Marketing campaigns
- Anomaly detection
 - Outliers
- Semi-supervised learning
 - Propagate limited labels
- Image segmentation
 - · Object detection








Semi-supervised learning

- Labelling training data is a bottleneck of supervised learning
- Handwritten digits 0,1,...,9
 - 1797 images
- Standard logistic regression model has 96.9% accuracy
- Suppose we take 50 random samples as training set
- Logistic regression gives 83.3%





Semi-supervised learning

- Instead of 50 random samples, 50 clusters using K means
- Use image nearest to each centroid as training set
 - 50 representative images
- Logistic regression accuracy jumps to 92.2%



Semi-supervised learning



- Propagate representative image label to entire cluster
 92.2 %
- Logistic regression improves to 93.3%
- Propagage representive image label to only 20% items closest to centroid
- Logistic regression improves to 94%
- Only 50 actual labels used, about 5 per class!









- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours





- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change

10 colors





- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change
- Same with 8

8 colors





- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change
- Same with 8
- At 6 colours, ladybug red goes

6 colors





- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change
- Same with 8
- At 6 colours, ladybug red goes
- 4 colours

4 colors





- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change
- Same with 8
- At 6 colours, ladybug red goes
- 4 colours
- Finally 2 colours, flower and rest







Summary

- Unsupervised learning is useful as a preprocessing step
- Semi supervised learning
 - Identify a small subset of items to label manually
 - Propagate labels via cluster
- Image segmentation
 - Highlight objects by colour

