

Lecture 13: 3 March, 2026


Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Data Mining and Machine Learning
January–April 2026


Unsupervised learning

- Supervised learning requires labelled data



Unsupervised learning

- Supervised learning requires labelled data
- Vast majority of data is unlabelled
- What insights can you get with unlabelled data?




Unsupervised learning

- Supervised learning requires labelled data
- Vast majority of data is unlabelled
- What insights can you get with unlabelled data?

*“If intelligence was a cake,
unsupervised learning would be the
cake, supervised learning would be
the icing on the cake ...”*

– Yann LeCun
ACM Turing Award 2018



Applications

- Customer segmentation
 - Marketing campaigns



Applications

- Customer segmentation
 - Marketing campaigns
- Anomaly detection
 - Outliers



Applications

- Customer segmentation
 - Marketing campaigns
- Anomaly detection
 - Outliers
- Semi-supervised learning
 - Propagate limited labels




Applications

- Customer segmentation
 - Marketing campaigns
- Anomaly detection
 - Outliers
- Semi-supervised learning
 - Propagate limited labels
- Image segmentation
 - Object detection




Clustering

- Find natural groups of data





Clustering

- Find natural groups of data
- Define a distance measure





Clustering

- Find natural groups of data
- Define a distance measure
- Group together data that is close together





Clustering

- Find natural groups of data
- Define a distance measure
- Group together data that is close together
- Top down
 - Partition data into clusters



Clustering



- Find natural groups of data
- Define a distance measure
- Group together data that is close together
- Top down
 - Partition data into clusters
- Bottom up
 - Group items into clusters



Top down clustering



no. of clusters
K Means Clustering *Average*

- Data items are points in n dimensions
 - (x_1, x_2, \dots, x_n)





K Means Clustering

- Data items are points in n dimensions
 - (x_1, x_2, \dots, x_n)
- Partition into K clusters
 - Fix K in advance



K Means Clustering


- Data items are points in n dimensions
 - (x_1, x_2, \dots, x_n)
- Partition into K clusters
 - Fix K in advance
- Each cluster is represented by its geometric centre
 - Centroid, or mean
 - Hence “ K means”



K Means Algorithm


- Choose K points initially as random centroids

K=2




K Means Algorithm

- Choose K points initially as random centroids
- In each iteration
 - Assign each point to nearest centroid
 - Recompute centroids




K Means Algorithm

- Choose K points initially as random centroids
- In each iteration
 - Assign each point to nearest centroid
 - Recompute centroids




K Means Algorithm

- Choose K points initially as random centroids
- In each iteration
 - Assign each point to nearest centroid
 - Recompute centroids




K Means Algorithm

- Choose K points initially as random centroids
- In each iteration
 - Assign each point to nearest centroid
 - Recompute centroids




K Means Algorithm

- Choose K points initially as random centroids
- In each iteration
 - Assign each point to nearest centroid
 - Recompute centroids



K Means Algorithm

- Choose K points initially as random centroids
- In each iteration
 - Assign each point to nearest centroid
 - Recompute centroids



K Means Algorithm

- Choose K points initially as random centroids
- In each iteration
 - Assign each point to nearest centroid
 - Recompute centroids
- Termination
 - Clusters stabilize
 - Sum square distance is below threshold

Evaluating clustering

- How “tight” are the clusters?

Evaluating clustering

- How “tight” are the clusters?
- Mean squared distance from centroids —
inertia


$$\frac{1}{n} \sum_{j=1}^K \sum_{x \in C_j} \text{distance}(x, \text{centroid}_j)^2$$

Evaluating clustering

- How “tight” are the clusters?
- Mean squared distance from centroids — **inertia**

$$\frac{1}{n} \sum_{j=1}^K \sum_{x \in C_j} \text{distance}(x, \text{centroid}_j)^2$$

- Plot inertia for different values of K and look for optimum




Evaluating clustering

- How “tight” are the clusters?
- Mean squared distance from centroids —
inertia

$$\frac{1}{n} \sum_{j=1}^K \sum_{x \in C_j} \text{distance}(x, \text{centroid}_j)^2$$

- Plot inertia for different values of K and look for optimum
- Can also use change in inertia threshold to stop iterations



K Means Algorithm

Advantages

- Efficient — each iteration makes a single pass over data
 - Incrementally compute centroid

$$\frac{n \times \text{Avg to } n + V_{n+1}}{n+1}$$

K Means Algorithm

Advantages

- Efficient — each iteration makes a single pass over data
 - Incrementally compute centroid

Disadvantages


K Means Algorithm

Advantages

- Efficient — each iteration makes a single pass over data
 - Incrementally compute centroid

Disadvantages

- Can only find clusters that look like ellipses




K Means Algorithm

Advantages

- Efficient — each iteration makes a single pass over data
 - Incrementally compute centroid

Disadvantages

- Can only find clusters that look like ellipses




K Means Algorithm

Advantages

- Efficient — each iteration makes a single pass over data
 - Incrementally compute centroid

Disadvantages

- Can only find clusters that look like ellipses
- Choice of initial random centroid matters
 - Repeat and check



K Means Algorithm


Advantages

- Efficient — each iteration makes a single pass over data
 - Incrementally compute centroid

Disadvantages

- Can only find clusters that look like ellipses
- Choice of initial random centroid matters
 - Repeat and check

Heuristics to choose initial centroids




Hierarchical clustering

- K Means clustering can only find clusters that look like ellipses
- Instead, build clusters bottom up, by merging clusters


Hierarchical clustering

- K Means clustering can only find clusters that look like ellipses
- Instead, build clusters bottom up, by merging clusters
- Initially, each item is a singleton cluster
- At each step, merge nearest clusters




Hierarchical clustering

- K Means clustering can only find clusters that look like ellipses
- Instead, build clusters bottom up, by merging clusters
- Initially, each item is a singleton cluster
- At each step, merge nearest clusters
- Can represent process using a tree — **dendrogram**
- Choose appropriate level in dendrogram for final clustering



Hierarchical clustering

- K Means clustering can only find clusters that look like ellipses
- Instead, build clusters bottom up, by merging clusters
- Initially, each item is a singleton cluster
- At each step, merge nearest clusters
- Can represent process using a tree — **dendrogram**
- Choose appropriate level in dendrogram for final clustering




Hierarchical Clustering

To merge clusters, define distance between clusters

Hierarchical Clustering

To merge clusters, define distance between clusters


- Single link: distance between closest points
 - Creates chain effect



Hierarchical Clustering

To merge clusters, define distance between clusters


- Single link: distance between closest points
 - Creates chain effect
- Complete link: maximum of pairwise distances



Hierarchical Clustering

To merge clusters, define distance between clusters


- Single link: distance between closest points
 - Creates chain effect
- Complete link: maximum of pairwise distances
- Average link: mean of pairwise distances



Hierarchical Clustering


To merge clusters, define distance between clusters

- Single link: distance between closest points
 - Creates chain effect
- Complete link: maximum of pairwise distances
- Average link: mean of pairwise distances
- All require $O(n^2)$ computation — expensive





Clustering

- How to identify odd shaped clusters?
- Cluster — group of points that are “close together”
- Identify “dense” neighbourhoods
- How do we formalize this?




Density based clustering

- Construct a small ball around each point, radius Eps
- Identify a threshold for neighbours within ball, $MinPts$




Density based clustering

- Construct a small ball around each point, radius Eps
- Identify a threshold for neighbours within ball, $MinPts$
- **Core point** — has at least $MinPts$ neighbours inside Eps ball




Density based clustering

- Construct a small ball around each point, radius Eps
- Identify a threshold for neighbours within ball, $MinPts$
- **Core point** — has at least $MinPts$ neighbours inside Eps ball
- Connect each core point to all its neighbours → *Directed edge*




Density based clustering


- Construct a small ball around each point, radius Eps
- Identify a threshold for neighbours within ball, $MinPts$
- **Core point** — has at least $MinPts$ neighbours inside Eps ball
- Connect each core point to all its neighbours
- **Border points** — attached to core points but not core themselves



Density based clustering

- Construct a small ball around each point, radius Eps
- Identify a threshold for neighbours within ball, $MinPts$
- **Core point** — has at least $MinPts$ neighbours inside Eps ball
- Connect each core point to all its neighbours
- **Border points** — attached to core points but not core themselves
- **Noise** — isolated, disconnected points






μ_1, μ_2
 σ_1, σ_2

Density based clustering


- Formally, edges from core points to neighbours define a directed graph
- Border points are part of this graph, but cannot add edges to extend the graph
- Discard the edge directions
- Connected components are clusters



- Implementation of density based clustering available in Python and R

Dbscan


- Implementation of density based clustering available in Python and R
- Smaller value of Eps subdivides into small clusters




Dbscan

- Implementation of density based clustering available in Python and R
- Smaller value of Eps subdivides into small clusters
- Larger Eps groups larger clusters

eps=0.05, min_samples=5



eps=0.20, min_samples=5




Outliers and clustering

- Outliers are anomalous values


Outliers and clustering

- Outliers are anomalous values
- **K** Means — lie outside natural clusters, far from all centroids





Outliers and clustering

- Outliers are anomalous values
- **K** Means — lie outside natural clusters, far from all centroids
 - But outliers can distort the clustering process





Outliers and clustering

- Outliers are anomalous values
- **K** Means — lie outside natural clusters, far from all centroids
 - But outliers can distort the clustering process
- Density based clustering — not connected to any core point
 - But density is applied uniformly



Outliers and clustering

- Outliers are anomalous values
- **K** Means — lie outside natural clusters, far from all centroids
 - But outliers can distort the clustering process
- Density based clustering — not connected to any core point
 - But density is applied uniformly
- How to identify outliers before clustering?




Outliers and density

- An outlier is less dense than its nearest neighbours


Outliers and density

- An outlier is less dense than its nearest neighbours
- But difference in density may be local




Outliers and density

- An outlier is less dense than its nearest neighbours
- But difference in density may be local
- A distance metric to eliminate o_2 could make all of C_1 outliers



Outliers and density

- An outlier is less dense than its nearest neighbours
- But difference in density may be local
- A distance metric to eliminate o_2 could make all of C_1 outliers
- C_1 has 400 points, C_2 has 100 points
- Larger distance would make all of C_2 outliers with respect to C_1




Outliers and density

- For clustering, we defined a radius Eps and looked for $MinPts$ neighbours within that ball


Outliers and density

- For clustering, we defined a radius Eps and looked for $MinPts$ neighbours within that ball
- Instead, fix $MinPts$ and find smallest ball with that many neighbours




Outliers and density

- For clustering, we defined a radius Eps and looked for $MinPts$ neighbours within that ball
- Instead, fix $MinPts$ and find smallest ball with that many neighbours
- Compare $radius(p)$ with radius of its neighbours



Outliers and density

- For clustering, we defined a radius Eps and looked for $MinPts$ neighbours within that ball
- Instead, fix $MinPts$ and find smallest ball with that many neighbours
- Compare $radius(p)$ with radius of its neighbours
- A is an outlier because its radius is much more than that of its neighbours



Outliers and density

- Local outlier factor $LOF(p)$

$$\frac{\text{Mean radius of } \text{MinPts-neighbours}(p)}{\text{radius}(p)}$$

- The smaller this ratio, the more likely that p is an outlier
- Comparison is local to neighbourhood, so this can deal with different densities across range of data

