

Analysis of algorithms

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python

Week 2

Measuring performance

- Example of validating SIM cards against Aadhaar data
 - Naive approach takes thousands of years
 - Smarter solution takes a few minutes

Measuring performance

- Example of validating SIM cards against Aadhaar data
 - Naive approach takes thousands of years
 - Smarter solution takes a few minutes
- Two main resources of interest
 - Running time — how long the algorithm takes
 - Space — memory requirement

Measuring performance

- Example of validating SIM cards against Aadhaar data
 - Naive approach takes thousands of years
 - Smarter solution takes a few minutes
- Two main resources of interest
 - Running time — how long the algorithm takes
 - Space — memory requirement
- Time depends on processing power
 - Impossible to change for given hardware
 - Enhancing hardware has only a limited impact at a practical level

Measuring performance

- Example of validating SIM cards against Aadhaar data
 - Naive approach takes thousands of years
 - Smarter solution takes a few minutes
- Two main resources of interest
 - Running time — how long the algorithm takes
 - Space — memory requirement
- Time depends on processing power
 - Impossible to change for given hardware
 - Enhancing hardware has only a limited impact at a practical level
- Storage is limited by available memory
 - Easier to configure, augment

Measuring performance

- Example of validating SIM cards against Aadhaar data
 - Naive approach takes thousands of years
 - Smarter solution takes a few minutes
- Two main resources of interest
 - Running time — how long the algorithm takes
 - Space — memory requirement
- Time depends on processing power
 - Impossible to change for given hardware
 - Enhancing hardware has only a limited impact at a practical level
- Storage is limited by available memory
 - Easier to configure, augment
- Typically, we focus on time rather than space

Input size

- Running time depends on input size
 - Larger arrays will take longer to sort

Input size

- Running time depends on input size
 - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
 - Input size n
 - Running time $t(n)$

Input size

- Running time depends on input size
 - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
 - Input size n
 - Running time $t(n)$
- Different inputs of size n may take different amounts of time
 - We will return to this point later

Input size

- Running time depends on input size
 - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
 - Input size n
 - Running time $t(n)$
- Different inputs of size n may take different amounts of time
 - We will return to this point later

Example 1 SIM cards vs Aadhaar cards

- $n \approx 10^9$ — number of cards

Input size

- Running time depends on input size
 - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
 - Input size n
 - Running time $t(n)$
- Different inputs of size n may take different amounts of time
 - We will return to this point later

Example 1 SIM cards vs Aadhaar cards

- $n \approx 10^9$ — number of cards
- Naive algorithm: $t(n) \approx n^2$

- Running time depends on input size
 - Larger arrays will take longer to sort
- Measure time efficiency as function of input size
 - Input size n
 - Running time $t(n)$
- Different inputs of size n may take different amounts of time
 - We will return to this point later

Example 1 SIM cards vs Aadhaar cards

- $n \approx 10^9$ — number of cards
- Naive algorithm: $t(n) \approx n^2$
- Clever algorithm: $t(n) \approx n \log_2 n$
 - $\log_2 n$ — number of times you need to divide n by 2 to reach 1
 - $\log_2(n) = k \Rightarrow n = 2^k$

Example 2 Video game

- Several objects on screen

Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects

Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- n objects — naive algorithm is n^2
 - For each pair of objects, compute their distance
 - Report minimum distance across all pairs

Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- n objects — naive algorithm is n^2
 - For each pair of objects, compute their distance
 - Report minimum distance across all pairs
- There is a clever algorithm that takes time $n \log_2 n$

Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- n objects — naive algorithm is n^2
 - For each pair of objects, compute their distance
 - Report minimum distance across all pairs
- There is a clever algorithm that takes time $n \log_2 n$
- High resolution gaming console may have 4000x2000 pixels
 - 8×10^6 points — 8 million

Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- n objects — naive algorithm is n^2
 - For each pair of objects, compute their distance
 - Report minimum distance across all pairs
- There is a clever algorithm that takes time $n \log_2 n$
- High resolution gaming console may have 4000×2000 pixels
 - 8×10^6 points — 8 million
- Suppose we have $100,000 = 1 \times 10^5$ objects

Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- n objects — naive algorithm is n^2
 - For each pair of objects, compute their distance
 - Report minimum distance across all pairs
- There is a clever algorithm that takes time $n \log_2 n$
- High resolution gaming console may have 4000×2000 pixels
 - 8×10^6 points — 8 million
- Suppose we have $100,000 = 1 \times 10^5$ objects
- Naive algorithm takes 10^{10} steps
 - 1000 seconds, or 16.7 minutes in Python
 - Unacceptable response time!

Example 2 Video game

- Several objects on screen
- Basic step: find closest pair of objects
- n objects — naive algorithm is n^2
 - For each pair of objects, compute their distance
 - Report minimum distance across all pairs
- There is a clever algorithm that takes time $n \log_2 n$
- High resolution gaming console may have 4000×2000 pixels
 - 8×10^6 points — 8 million
- Suppose we have $100,000 = 1 \times 10^5$ objects
- Naive algorithm takes 10^{10} steps
 - 1000 seconds, or 16.7 minutes in Python
 - Unacceptable response time!
- $\log_2 100,000$ is under 20, so $n \log_2 n$ takes a fraction of a second

Orders of magnitude

- When comparing $t(n)$, focus on orders of magnitude
 - Ignore constant factors

Orders of magnitude

- When comparing $t(n)$, focus on orders of magnitude
 - Ignore constant factors
- $f(n) = n^3$ eventually grows faster than $g(n) = 5000n^2$
 - For small values of n , $f(n) < g(n)$
 - After $n = 5000$, $f(n)$ overtakes $g(n)$

Orders of magnitude

- When comparing $t(n)$, focus on orders of magnitude
 - Ignore constant factors
- $f(n) = n^3$ eventually grows faster than $g(n) = 5000n^2$
 - For small values of n , $f(n) < g(n)$
 - After $n = 5000$, $f(n)$ overtakes $g(n)$
- **Asymptotic complexity**
 - What happens in the limit, as n becomes large

Orders of magnitude

- When comparing $t(n)$, focus on orders of magnitude
 - Ignore constant factors
- $f(n) = n^3$ eventually grows faster than $g(n) = 5000n^2$
 - For small values of n , $f(n) < g(n)$
 - After $n = 5000$, $f(n)$ overtakes $g(n)$
- **Asymptotic complexity**
 - What happens in the limit, as n becomes large
- Typical growth functions
 - Is $t(n)$ proportional to $\log n, \dots, n^2, n^3, \dots, 2^n$?
 - Note: $\log n$ means $\log_2 n$ by default
 - Logarithmic, polynomial, exponential, ...

Orders of magnitude

Input size	Values of $t(n)$						
	$\log n$	n	$n \log n$	n^2	n^3	2^n	$n!$
10	3.3	10	33	100	1000	1000	10^6
100	6.6	100	66	10^4	10^6	10^{30}	10^{157}
1000	10	1000	10^4	10^6	10^9		
10^4	13	10^4	10^5	10^8	10^{12}		
10^5	17	10^5	10^6	10^{10}			
10^6	20	10^6	10^7	10^{12}			
10^7	23	10^7	10^8				
10^8	27	10^8	10^9				
10^9	30	10^9	10^{10}				
10^{10}	33	10^{10}	10^{11}				

Measuring running time

- Analysis should be independent of the underlying hardware
 - Don't use actual time
 - Measure in terms of **basic operations**

Measuring running time

- Analysis should be independent of the underlying hardware
 - Don't use actual time
 - Measure in terms of **basic operations**
- Typical basic operations
 - Compare two values
 - Assign a value to a variable

Measuring running time

- Analysis should be independent of the underlying hardware
 - Don't use actual time
 - Measure in terms of **basic operations**
- Typical basic operations
 - Compare two values
 - Assign a value to a variable
- Exchange a pair of values?

```
(x,y) = (y,x)    t = x
                  x = y
                  y = t
```

- If we ignore constants, focus on orders of magnitude, both are within a factor of 3
- Need not be very precise about defining basic operations

What is the input size

- Typically a natural parameter
 - Size of a list/array that we want to search or sort
 - Number of objects we want to rearrange
 - Number of vertices and number edges in a graph
 - We shall see why these are separate parameters

What is the input size

- Typically a natural parameter
 - Size of a list/array that we want to search or sort
 - Number of objects we want to rearrange
 - Number of vertices and number edges in a graph
 - We shall see why these are separate parameters
- What about numeric problems? Is n a prime?

What is the input size

- Typically a natural parameter
 - Size of a list/array that we want to search or sort
 - Number of objects we want to rearrange
 - Number of vertices and number edges in a graph
 - We shall see why these are separate parameters
- What about numeric problems? Is n a prime?
 - Magnitude of n is not the correct measure

What is the input size

- Typically a natural parameter
 - Size of a list/array that we want to search or sort
 - Number of objects we want to rearrange
 - Number of vertices and number edges in a graph
 - We shall see why these are separate parameters
- What about numeric problems? Is n a prime?
 - Magnitude of n is not the correct measure
 - Arithmetic operations are performed digit by digit
 - Addition with carry, subtraction with borrow, multiplication, long division ...

What is the input size

- Typically a natural parameter
 - Size of a list/array that we want to search or sort
 - Number of objects we want to rearrange
 - Number of vertices and number edges in a graph
 - We shall see why these are separate parameters
- What about numeric problems? Is n a prime?
 - Magnitude of n is not the correct measure
 - Arithmetic operations are performed digit by digit
 - Addition with carry, subtraction with borrow, multiplication, long division ...
 - Number of digits is a natural measure of input size
 - Same as $\log_b n$, when we write n in base b

Which inputs should we consider?

- Performance varies across input instances
 - By luck, the value we are searching for is the first element we examine in an array

Which inputs should we consider?

- Performance varies across input instances
 - By luck, the value we are searching for is the first element we examine in an array
- Ideally, want the “average” behaviour
 - Difficult to compute
 - Average over what? Are all inputs equally likely?
 - Need a probability distribution over inputs

Which inputs should we consider?

- Performance varies across input instances
 - By luck, the value we are searching for is the first element we examine in an array
- Ideally, want the “average” behaviour
 - Difficult to compute
 - Average over what? Are all inputs equally likely?
 - Need a probability distribution over inputs
- Instead, **worst case** input
 - Input that forces algorithm to take longest possible time
 - Search for a value that is not present in an unsorted list
 - Must scan all elements

Which inputs should we consider?

- Performance varies across input instances
 - By luck, the value we are searching for is the first element we examine in an array
- Ideally, want the “average” behaviour
 - Difficult to compute
 - Average over what? Are all inputs equally likely?
 - Need a probability distribution over inputs
- Instead, **worst case** input
 - Input that forces algorithm to take longest possible time
 - Search for a value that is not present in an unsorted list
 - Must scan all elements
 - Pessimistic — worst case may be rare

Which inputs should we consider?

- Performance varies across input instances
 - By luck, the value we are searching for is the first element we examine in an array
- Ideally, want the “average” behaviour
 - Difficult to compute
 - Average over what? Are all inputs equally likely?
 - Need a probability distribution over inputs
- Instead, **worst case** input
 - Input that forces algorithm to take longest possible time
 - Search for a value that is not present in an unsorted list
 - Must scan all elements
 - Pessimistic — worst case may be rare
 - Upper bound for worst case **guarantees** good performance

Summary

- Two important parameters when measuring algorithm performance
 - Running time, memory requirement (space)
 - We mainly focus on time

Summary

- Two important parameters when measuring algorithm performance
 - Running time, memory requirement (space)
 - We mainly focus on time
- Running time $t(n)$ is a function of input size n
 - Interested in orders of magnitude
 - Asymptotic complexity, as n becomes large

Summary

- Two important parameters when measuring algorithm performance
 - Running time, memory requirement (space)
 - We mainly focus on time
- Running time $t(n)$ is a function of input size n
 - Interested in orders of magnitude
 - Asymptotic complexity, as n becomes large
- From running time, we can estimate feasible input sizes

Summary

- Two important parameters when measuring algorithm performance
 - Running time, memory requirement (space)
 - We mainly focus on time
- Running time $t(n)$ is a function of input size n
 - Interested in orders of magnitude
 - Asymptotic complexity, as n becomes large
- From running time, we can estimate feasible input sizes
- We focus on worst case inputs
 - Pessimistic, but easier to calculate than average case
 - Upper bound on worst case gives us an overall guarantee on performance